

ONDUVILLA® CLOSURE CAP

TECHNICAL DATA SHEET

APPLICATION

The CLOSURE CAP is a special type of SLIM CAP which is closed on one side.

It is used to provide a neat finish of the ridge and hip lines, and also prevents birds or other small animals to enter into the roof space.

TECHNICAL CHARACTERISTICS

Made of cellulosic fibers, natural pigments and bitumen.
Manufactured using molding process (patented technology).

Length	106 cm
Width	18 cm
Height	8 cm
Thickness	2,2 mm
Weight (pigmented/painted)	0,61 / 0,64 kg

PACKAGING

Full range matching all ONDUVILLA® colours (pigmented/painted).
Box 20 pcs
Pallet 20 boxes (400 pcs)

HANDLING AND STORAGE

The product should be protected from direct sunlight and be stored dry.

INSTALLATION

The CLOSURE CAP is applied using the same method as the SLIM CAP.
For specific roof details, please refer to ONDUVILLA® fixing guide.

WARRANTY

Watertightness is guaranteed for 15 years.

All the claims will be considered with respect to application recommendations issued by Onduline company.



Where CLOSURE CAP is used

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

ONDULINE AVRASYA
Değirmen Sokak Nida Kule İş Mrk.
No:18 Kat:8 34742 Kozyatağı, Kadıköy/ İSTANBUL
Tel.: +90 216 384 16 00 pbx.
Fax: +90 216 384 16 10

www.onduline.com.tr

Onduline®